

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/014292 A2

(51) International Patent Classification⁷: B41J 2/14, 2/16

(21) International Application Number:
PCT/GB2004/003109

(22) International Filing Date: 19 July 2004 (19.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0316934.9 19 July 2003 (19.07.2003) GB

(71) Applicant (for all designated States except US): XAAR
TECHNOLOGY LIMITED [GB/GB]; Science Park,
Cambridge CB4 0XR (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): DRURY, Paul, Ray-
mond [GB/GB]; 8 New Road, Great Chishill, Royston,
Hertfordshire SG8 8ST (GB).

(74) Agents: GARRATT, Peter, Douglas et al.; Mathys &
Squire, 100 Gray's Inn Road, London WC1X 8AL (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF MANUFACTURING A COMPONENT FOR DROPLET DEPOSITION APPARATUS



(57) Abstract: A nozzle plate component is manufactured by forming a layer of photoresist on a substrate and selectively exposing and removing material to define an array of distinct bodies. Nickel is then electroformed around the bodies to form a plate, with nozzles subsequently formed by ablation through the photoresist. The process can essentially be repeated to form a guard structure around each nozzle.

WO 2005/014292 A2